

# Clear teacher instruction throughout the classroom. Alerts and voice calls from anywhere in the school.

With network connectivity and integrations with building communication systems, teachers can quickly initiate an alert, or call the front office directly from their microphone.



Full-featured audio amplifier with network connection and PoE+



Clearmike

Comfortable teacher microphone amplifies the voice and initiates alerts



Web Console

Supports, monitors and updates your hardware

#### **LEARNING BEGINS WITH LISTENING**

Combined with Clearmike and speakers, Cascadia delivers all the benefits of instructional audio:

- Even distribution of the teacher's voice
- Integration with classroom multimedia
- Supports student sharing with second mic

#### SAFETY, MOBILITY AND IMMEDIACY

Integrate with your existing building communication systems to:

- Initiate a silent emergency alert
- Make two-way calls to the office
- Send from anywhere in the building

### **CENTRALIZED CONTROL SAVES TIME**

Cascadia Web Console provides centralized visibility and control:

- Support and monitor your hardware
- Manage your integrations
- Push updates to your equipment
- Locate the teacher during an active alert

BARRIERS TO LISTENING







HEARING LOSS

MASKS



**CREATING BETTER** ACCESS TO LEARNING

INCREASE ON STANDFORD ACHEIVEMENT TEST

HIGHED **ELL WORD** RECOGNITION

LESS BEHAVIOR

REDIRECTIONS

NETWORKED INSTRUCTIONAL AUDIO SYSTEM

O O O Stript


### **Instructional Technology** Connect with other classroom technologies to provide clear and even distribution of all audio.

# Network Connectivity

Network connectivity with PoE+

## **Life-Safety & Communication**

Integrate with building communication systems to unlock critical functionality when help is needed.



Approximate incident location on a school map

C25 Description	Wireless audio hub
Wireless Communication	Access Technology (1.9 GHz)
Frequency Response	20 Hz - 20 kHz Power Amp, 150 Hz - 6.5 kHz Wireless
Power Supply Options	24VDC/2.5A or PoE+ 802.3at
Power Output	40 WRMS total (20 WRMS/channel) with 24VDC supply
Tone Control	Bass/Treble control
Ethernet	10/100Mbps
Audio Inputs	Three (3) 3.5mm inputs, one S/PDIF coaxial digital input
Audio Output	One (1) 3.5mm output, one S/PDIF coaxial digital output
Maximum Input/Output Level	1.4VRMS / 1.4VRMS
Total Harmonic Distortion	<1%
Analog Control Signals	Inputs: PageFirst (25/70V page mute), Relay Input
	Output: Contact closure (initiated from microphone)
$\textbf{Dimensions} \; (W  X  H  X  D)$	9.0" x 6.1" x 1.2" (229mm x 155mm x 30mm)
Weight	17.5 oz (496g)

### SPEAKERS AND OPTIONS



MULTIMEDIA CEILING SPEAKER







Sharemike HANDHELD STUDENT MIC



LEARNING

